

RESIN GRIP FINE

Broadcast Aggregate for Non-slip PU Topcoat

DESCRIPTION

A hard, white broadcast particle used to create a non-slip finish in clear polyurethane topcoats.

Aluminium oxide is selected for superior impact and wear resistance. Its Mohs hardness of 9 is bettered only by diamond (10), and allows the installation of hardwearing non-slip surfaces with far greater durability than sand.

USES

Suitable for use in Ezipoly and other PU topcoats.

PRODUCT DETAILS

Type: Aluminium oxide.
Colour: White.
Pack Size: 1kg.



BENEFITS

- ✓ Extremely hard for maximum durability.
- ✓ White colour keeps floor looking good as it wears.
- ✓ Suitable for use in clear coatings.
- ✓ Packaged in easy-to-handle 1kg tubs.

APPLICATION

Broadcast immediately after topcoat application. Grab a “knuckle full” and gently toss onto the surface in a chicken feeding motion. Once broadcast, wet backroll the topcoat to evenly spread and encapsulate the non-slip particles.

Consumption is typically 70-100g/m².

PRODUCT NOTES

- Do not broadcast excessive amounts of Resin Grip particle as it can result in clumping of aggregate.
- For best results, use in combination with Ezipoly applied at 100-microns (10m²/L).
- Level of non-slip achieved will depend on evenness of broadcast and thickness of topcoat film.

STORAGE

Keep containers closed when not in use. Seek advice from your local council regarding accepted disposal methods.

FIRST AID

CAUTION: KEEP OUT OF REACH OF CHILDREN.

IF ON SKIN: Rinse skin after manually handling and wash contaminated clothing before re-use. IF IN EYES: Rinse cautiously with water for several minutes. IF INHALED: Remove person to fresh air. IF exposed, concerned, unwell or irritation persists: Get medical advice/attention.